Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	: Wiz
--------------------------------	-------

Supplier's address: WIZ, WIZ I.B.R.S. / C.C.R.I. Number 10461, 5600VB Eindhoven, NL

Model identifier: 9290023836AW

_	•			
Type	Λt	liont	COLL	rca.
IVDE	VI.	HEIL	3UU	ıcc.

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E27		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	Yes
Colour-tuneable light source:	Yes	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters

		Froduct parar	neters	
Parameter		Value	Parameter	Value
	General product parameters:			
O ,	mption in on- 100 h), rounded st integer	8	Energy efficiency class	F
indicating if it r in a sphere (3	us flux (фuse), refers to the flux 60º), in a wide in a narrow cone	806 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	22006500
On-mode pressed in W	oower (P _{on}),	8,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,50
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		0,50	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90
Outer	Height	122	Spectral power	See image
dimensions	Width	60	distribution in the	in last page
		·		Page 1/3

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	60	range 250 nm to 800 nm, at full-load	
Claim of equival	ent power ^(a)	Yes	If yes, equivalent power (W)	60
			Chromaticity coordinates (x and y)	0,458
Parameters for	LED and OLED lig	ht sources:		
R9 colour rende	ring index value	0	Survival factor	0,90
the lumen main	tenance factor	0,96		
Parameters for LED and OLED mains light sources:				
displacement fa	ctor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6
	-	_(b)	If yes then replacement claim (W)	-
Flicker metric (P	st LM)	1,0	Stroboscopic effect metric (SVM)	0,4

(a)'-': not applicable; (b)'-': not applicable;

